

HANDICAPPED SPACES, DOUBLE TYPE

NOTES:

- 1. The parking stalls shall be marked with 4" blue thermoplastic stripes and a white handicap logo on a blue 3'x 3' background square in each stall. (see Detail No. ST-6)
- 2. Parking stalls next to fences, walls, sidewalk or structures may be required to contain wheel stops, curbs or other protective devices.
- 3. Wheel chair users must not be forced to go behind parked cars other than
- 4. Handicapped space must permit use of either car door.
- 5. One in every eight (8) accessible spaces but not less than one shall be served by an Access Isle 132" wide min. and shall be designated 'Van Accessible" as required.
- Required number of accessible Parking spaces shall conform to both, the federal and state guidlines, rules and regulations. Van Accessible" as required.


## IDENTIFICATION OF HANDICAPPED SPACES:

Each parking space reserved for the handicapped shall be identified by a permanently affixed reflectorized metal sign displaying the international symbol of accessibility. The sign shall not be smaller than 12"x18' and shall be centered at the interior end of the parking space at a minimum grade, or centered on the wall at the interior end of the parking space at a minimum height of 36" from the parking space finished grade, ground, or sidewalk.

A street sign shall also be posted, in a conspicuous place, at each entrance to the off street parking facility, not less than 17" x 22" in size with lettering not less than 1" in height, which clearly and conpicuously states the following:

Unauthorized vehicles not displaying distinguishing placards or license plates issued for physically handicapped persons may be towed away at owner's expense. Towed vehicles may be reclaimed at the Menlo Park Police Department or by telephoning (415) 858 - 3300.

In addition to the above requirements, the surface of each parking place shall have a suface identification duplicating the symbol of accessibility in white paint on a blue background, 3 feet 6 inch square.



## HANDICAPPED PARKING SIGN INSTALLATION

## NOTES:

- 1. Sign location subject to review and approval by Transportation Manager.
- 2. Provide a reflectorize (R99) sign in front of all handicapped parking spaces.
- 3. Handicapped parking sign (R99) shall be per Caltrans sign specification sheet.



(EngDiv\CADSTNRD\Standard Details\ST-B (HandicapStail) Rev1.dwg